

Bio-presence Sensor Datasheet

Applicable Models:

Bioolgical Presence Sensor (TLIOT-BIOMS)

International standard home and building control system

Product feacture

Illuminance sensing function.

Human presence/motion.

sensitivity of the sensing function can be adjusted.

Networking function with master-slave sensor control.

Lux sensing function by 3 types of data output, the values of which can be sent cyclically.

motion monitoring function by 3 types of data output, values can be sent cyclically.

with on/off indicator function.


Valve (threshold)value (setting).

the function of prohibiting illuminance and movement


Technical parameters

DC 12V~30Vdc
< 50mA@24V DC
pressthe mask
24-24.25GHz
15dBm (max)
1.5-4m
1-3m
0-65535LUX
10-7200s
Ceiling /86 bottom box
1 lux~60k lux
-5°C~+45°C
-25°C~+55°C
-30°C~+70°C n

Dimension



Wiring Diagram



Instruction

- ①Illuminance sensor and programming integrated button: LED light flashing green: indicates that the radar has detected a human being; The LED light keeps red, the device is in programming
- 12-30V auxiliary power supply terminal
- KNX bus connection terminals

- 1. The installation and commissioning of equipment can only be operated by qualified skilled electricians. In the planning and implementation of electrical installations, the relevant standa rds, directives, rules and instructions must be strictly enforced;
 2. It is necessary to avoid moisture, dirt and damage in the process of
- transportation, storage and use;
- 3. Do not let the device run outside the specified technical indicators
- (such as temperature range);
 4. When the equipment is dirty, only use a dry cloth for cleaning. If this is not enough to clean, use a damp cloth dipped in a little soap solution to gently wipe without alkali or corrosive solvents.