



Screen receiver with software connection

TL-XM01

"Material: ABS, Input: 110-240V, Frequency: 433MHz, Clock
Battery: CR2032."

Applications

- Restaurants – For communication between servers and kitchen staff.
- Hospitals – To alert nurses and doctors for patient care or emergencies.
- Hotels – For staff coordination, such as housekeeping and concierge services.
- Factories – To notify workers about tasks or safety alerts.
- Retail Stores – For staff communication or customer service.
- Event Management – To coordinate between team members during large events.
- Warehouses – For stock management and team coordination.
- Care Homes – To alert caregivers to residents' needs.
- Security Services – For quick, discreet communication between security personnel.
- Office Buildings – For internal staff communication, especially in large facilities.

Features

- Standard alphanumeric keypad.
- 4-digit digital display.
- Initial digit configurable from A-F or 1-9.
- Displays up to three sets of call information simultaneously.
- Can be wall-mounted or placed on a desk.
- Reporting voice output supports multiple languages.
- Keywords can be entered in any text or language.
- Signal range varies from 150 to 250 meters in open environments, depending on the connected button.
- Reporting intervals can be customized.
- Adjustable cycle times for repeated operations.
- Ringtone can be pre-configured prior to manufacturing.
- Voice volume is fully adjustable.
- Powerbank charging is supported with an optional specialized cable (e.g., for beach use).
- Supports Wi-Fi connectivity for integration with computer software.