

Ceiling-mounted LED downlight



PART NO.	TL2009
DESCRIPTION	Ceiling-mounted downlight 30W
DATE	2024.10.21
Dimming optional	Phase /0-10V/Dali dimming

□ Datasheet:

Type	Product:	Ceiling-mounted Downlight
	Model No.:	TL2009
Electronical	Input Voltage:	220-240V/AC
	Frequency:	50/60Hz
	Power:	30W
	Power Factor:	0.9
	Total Harmonic Distortion:	<5%
	Certificates:	CE,Rohs,ERP
Optical	Cover Material:	PC
	Beam Angle:	20/40/60°
	LED Quantity:	1pcs
	LED Package:	Bridgelux
	Lu men:	800 lm
	Color Temperature:	3000/4000/5000K
	Color Render Index:	90/95
Lamp Structure	Housing Material:	Aluminium
	Diameter:	110*110*111mm
	Installation Hole:	powder painting
Surface Finish	Finished	(white color/customized color)
Watproof	IP	IP20
Others	Installation Type:	Surface mounted Type (refer to the Manual)
	Application:	Hotels, Supermarkets, Hospital, Aisles, Metro Station, Restaurants, Offices etc.
	Ambient Humidity:	≥80%R.H.
	Ambient Temperature :	-10 °C~+40°C -10 °C~50°C
	Storage Temperature :	-20
	Housing Temperature (working):	<70°C (Ta=25°C)
	Lifespan :	50000H
	Shape:	Square

Remarks:


1. All pictures&data above are only for your reference, models may slightly differ due to factory operation.
2. According to demand of Energy Star Rules and other Rules, Power Tolerance $\pm 10\%$ and CRI ± 5
3. Lumen Output Tolerance 10%
4. Beam Angle Tolerance $\pm 3^\circ$ (angle below 25°) or $\pm 5^\circ$ (angle above 25°)
5. All Data were gained at Ambient Temperature 25°C

□ **Dimension:** (unit:mm $\pm 2\text{mm}$, The following picture is a reference picture)

Model	Diameter ^① (caliber)	Diameter ^② (Maximum outer diameter)	Height ^③	Suggested Hole Cut	Net Weight (Kg)	Remark
TL2009	110	110	111	/	0.25	

□ **Installation:** (Notes on installation and wiring)

Please pay more attention to the below instructions while installation, in order to avoid any possible Fire Hazard, Electric Shock or Personal harm.



Instructions:

1. Cut off Electricity before installation.
2. Please do not block any objects on the lamp(distance scale within 70mm),which will definitely affect heat emission while lamp's working
3. Please double check before getting electricity on if wiring is100% OK, make sure Voltage for lamp is right and no Short-Circuit.

□ Wiring:

The Lamp can be directly connected to City Electric Supply and there'll be detailed User's Manual and Wiring Diagram.


Warning:

1. The Lamp is only for Indoor and Dry application, keep away from Heat, Steam, Wet, Oil, Corrosion etc, which may affect its permanence and shorten the lifespan.
2. Please strictly follow the instructions while installation to avoid any Hazard or damages.
3. Any installation, check or maintenance should be done by professional, please do not DIY if

without enough related knowledge.

4. For better and long performance, please clean the lamp at least every half year with soft cloth.
(Do not use Alcohol or Thinner as cleaner which may damage the lamp surface)
5. Do not expose the lamp under strong sunshine, heat source so rother high-temperature places,
and storage boxes cannot be piled up exceeding the requirements.

□ Carton Box Dimension:



Package	Dimension) LED
	Downlight
InnerBox	86*86*50mm
OuterBox	420*420*200mm 48PCS/carton
NetWeight	9.6kg
GrossWeight	11.8kg
Remarks: 1. If the loading qty less than 48pcs in a carton, pearl cotton material should be used to fill remaining space. 2. Accepted Loading Level is 6(refer to the actual shown on carton box) 3. The package can be as per customer's specific demand. 4. All package data are only for reference, it may be differ due to actual packing situation.	

Application:

Hotels, Supermarkets, Hospital, Aisles, Metro Station, Restaurants, Offices etc.